

Determination of Pour Points

with the

Pour Point Tester PPT 45150



Characteristics

- Accurate measurements according ASTM D5985
- Portable for -45 °C to +150 °C (-49 °F to +302 °F)
- In lab down to -55 °C/-67 °F
- Very fast cooling/heating by thermo-electrical modules
- Fully automated test procedure
- Repeated measurements
- Stand-alone device or use with PC

Fast and accurate

The Pour Point Tester PPT 45150 by PSL Systemtechnik provides pour point measurement of oils and oil products according to the rotational method ASTM D5985.

The test method permits pour point measurement with highest precision up to 0.1 °C at high repeatability.

Without additional cryostat the PPT covers a temperature range of -45 °C up to +150 °C (-49 °F to +302 °F).

New: Low temperature down to -55°C/-67°F

Our Pour Point Tester is now extendable with a cooling-water re cooler for temperatures down to -55 °C (-67 °F) - a cost-effective alternative to cryostats with the same capacity.

Repeated measurements

Pour point measurements can be repeated up to nine times in succession. We recommend those repeated measurements to obtain statistical significant results and information about the sample's behaviour over time.

Transportable in trolley case

Due to modern thermoelectric technology the PPT only needs tap water and a power supply. Therefore the PPT is excellently suited for operations outside the lab. The Pour Point Tester is equipped with a wide range voltage input so it can be operated all over the world.

Optionally, a trolley-case is available to transport the compact and lightweight Pour Point Tester as carry-on baggage.

Stand-alone device or use with PC

Of course, the PPT can also be used as a full-fledged lab instrument. Space-saving arranged, it can be operated as a stand-alone device or in conjunction with the software *WinPPT* via PC. With only few settings, you can start a fully automated test run.

Up to 10 test configurations can be saved on the instrument in stand-alone mode.



 **PSL Systemtechnik**
Germany

PSL Systemtechnik GmbH
Albrecht-von-Groddeck-Str. 5
D-38678 Clausthal-Zellerfeld
Germany

Telephone +49 5323 9627-90 · Fax +49 5323 9627-95 · info@psl-systemtechnik.de · www.psl-systemtechnik.de


An automated lab instrument

In combination with the PSL software *WinPPT* and a PC, you can execute fully automated test runs with the PPT. An unlimited number of test configurations can be saved and managed.

WinPPT permits comfortable control of test runs, data display and data saving in an Excel-compatible format for further

evaluation.

The temperature gradient gives you additional information about the behaviour of the sample. First crystallisation processes are as well observable as strong exothermal reactions.



Measurement example for automatic repeated pour point measurement

Specifications:

| | |
|----------------------------|---|
| Standard: | ASTM D 5985 |
| Temperature range: | -45 °C ... +150 °C (-49 °F ... +302 °F) at tap water 8 °C (46,4 °F), down to -55 °C (-49 °F) with re cooler |
| Resolution: | 0.1 °C |
| Accuracy: | < ± 0.4 K (± 0.2 K typical) |
| Cooling water usage: | 300 ml/min ... 800 ml/min |
| Cooling water pressure: | 1 bar ... 6 bar (14.5 psi ... 87 psi) |
| Cooling water temperature: | +3 °C ... +25 °C (+37 °F ... +86 °F), down to -20 °C (-4 °F) with re cooler |
| Power consumption: | 1,700 W |
| Voltage input: | 88 ... 264 V~ (47 ... 63 Hz) - wide range |
| Weight: | 9.5 kg, with trolley-case 14 kg |
| Dimensions (WxDxH): | 26 cm x 38 cm x 16 cm, height with sensor 43 cm |



PSL Systemtechnik GmbH
Albrecht-von-Groddeck-Str. 5
D-38678 Clausthal-Zellerfeld
Germany

Telephone +49 5323 9627-90 · Fax +49 5323 9627-95 · info@psl-systemtechnik.de · www.psl-systemtechnik.de